



**MINIMUM PAVEMENT SCHEDULE**

2" S9.5 C AT RATE OF 224 LBS/SY  
 3" B25.0 C AT RATE OF 342 LBS/SY  
 6" A.B.C.

**45' RIGHT OF WAY  
 26' ROADWAY SECTION  
 SECTION VIEW**

- NOTES:**
1. NORMAL CROWN OF 0.02' PER FOOT UNLESS OTHERWISE REQUIRED TO HAVE SUPERELEVATION.
  2. PAVEMENT DESIGN SHALL BE REQUIRED AND APPROVED BY NCDOT (FOR NCDOT ROADS) AND/OR CITY OF HENDERSONVILLE PRIOR TO PLACEMENT OF ANY BASE MATERIAL.
  3. PAVEMENT DESIGN SHALL BE AS SHOWN OR AS DESIGNED BY GEOTECHNICAL ENGINEER, WHICHEVER IS GREATER.
  4. TACK COAT SHALL BE APPLIED BENEATH EACH LAYER OF ASPHALT MIX TO BE PLACED AT A RATE OF 0.04 GAL/SY
  5. GRASS UTILITY STRIP REQUIRED UNLESS APPROVED BY PUBLIC WORKS DIRECTOR.
  6. FINAL SURFACE COURSE TO BE APPLIED UPON CITY OF HENDERSONVILLE APPROVAL.

**DATE: 05/19/2023**

**SCALE: NOT TO SCALE**      **WD DWG. NO. 04**

City of Hendersonville Engineering Department  
 305 Williams Street  
 Hendersonville, NC 28792  
 (828) 697-3000 (office)  
[www.cityofhendersonville.org](http://www.cityofhendersonville.org)

**STANDARD LOCAL STREET**

